

Nikon Digital Camera COOLPIX 5600/4600 Specifications

Type:	Digital camera E5600/E4600
Effective pixels:	5.1 million (E5600)/4.0 million (E4600)
CCD	E5600: 1/2.5-inch type (5.36 million total pixels) / E4600: 1/2.5-inch type (4.23 million total pixels)
Image modes:	E5600: High (2592*), Normal (2592), Normal (2048), PC (1024), TV (640) / E4600: High (2288*), Normal (2288), Normal (1600), PC (1024), TV (640)
Lens:	E5600: 3x Zoom-Nikkor; 5.7-17.1mm [35mm (135) format equivalent to 35-105mm]; f/2.9-4.9; 7 elements in 6 groups / E4600: 3x Zoom-Nikkor; 5.7-17.1mm [35mm (135) format equivalent to 34-102mm]; f/2.9-4.9; 7 elements in 6 groups; Digital zoom: up to 4x
LCD monitor:	1.8-inch type, 80,000-dot Amorphous silicon TFT LCD monitor with brightness adjustment
Storage media:	Internal memory: approx. 14MB, SD memory card
Shooting modes:	Auto, Scene Assist (Portrait, Landscape, Sports, Night portrait), Scene (Party/Indoor, Beach/Snow, Sunset, Dusk/Dawn, Night landscape, Close up, Museum, Fireworks show, Copy, Back light, Panorama assist, Underwater), BSS (Best Shot Selector), Blur Warning, Date imprint, Self-timer (10 sec.)
Movie:	E5600: with sound / E4600: without sound; TV movie (640) at 15fps, Small size (320) at 15fps, Smaller size (160) at 15fps
Capture modes:	1) Single, 2) Continuous (1.3fps; up to 3 frames), 3) Multi-shot 16 (16 frames 1/16 in size)
Number of frames:	E5600 (5M): (w/ Internal memory): High (2592*) approx. 5, Normal (2592) approx. 10 / E4600 (4M): (w/ Internal memory): High (2288*) approx. 7, Normal (2288) approx. 14
Built-in Speedlight:	Range: 0.4-3.3m / 1.3 - 10.8 ft. (W), 0.4-2.0m / 1.3 - 6.6 ft. (T); Flash modes: Auto, Auto with Red-eye Reduction (In-Camera Red-Eye Fix), Anytime Flash, Flash Cancel and Slow sync.
Interface:	USB
Supported languages:	German/English/Spanish/French/Italian/Dutch/Swedish/Japanese/Simplified Chinese/Traditional Chinese/Korean selectable in menu display
Power requirements:	Two EN-MH1 Rechargeable batteries, two LR6 (AA-size alkaline) batteries, two ZR6 (AA-size nickel manganese) batteries, two FR6 (AA-size lithium) batteries
Battery life (approx.):	E5600: 220 images with two AA-size alkaline batteries, 340 images with two EN-MH1 Rechargeable batteries/ E4600: 230 images with two AA-size alkaline batteries, 360 images with two EN-MH1 Rechargeable batteries (based on CIPA standard*)
Dimensions (W x H x D):	Approx. 85 x 60 x 35mm (3.3 x 2.4 x 1.4 in.)
Weight:	Approx. 130g (4.6 oz.) (without battery and memory card)
Supplied Accessories:†	Strap, USB cable, Audio Video cable (E5600), Video cable (E4600), Rechargeable Ni-MH Battery EN-MH1-B2, Battery charger MH-71, PictureProject CD-ROM
Optional Accessories:	AC adapter EH-62B, Ni-MH Rechargeable Battery EN-MH1-B2, Battery Charger MH-71, Soft case, Waterproof case WP-CP3‡

*Industry standard for measuring life of camera batteries. Measured at 25°C (77°F); zoom adjusted with each shot, built-in Speedlight fired with every other shot, image mode set to Normal.
†Supplied accessories may differ by country or area.
‡ Not available in some countries or areas.

PictureProject System Requirements

OS	Macintosh: Mac® OS X (10.1.5 or later)/ Windows: Windows® XP Home Edition / Professional, Windows® 2000 Professional, Windows® Me, Windows® 98SE pre-installed models
RAM	64MB (128MB with RAW images) or more recommended
Hard disk	60MB required for installation
Display	800 x 600 or larger with 16-bit color (full color recommended)
Others	CD-ROM drive required for installation Only built-in USB ports are supported

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh® and QuickTime® are either registered trademarks or trademarks of Apple Computer Inc. in the United States and/or other countries. The FotoNation logo is a trademark. The SD logo is a trademark. PictBridge is a trademark. D-Lighting technology is provided by Apical Limited. Products and brand names are trademarks or registered trademarks of their respective companies. Images on LCDs and monitors shown in this brochure are simulated. Sample images taken with the COOLPIX 5600. Some photos shot on location at La Vista Golf Resort.

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. January 2005 ©2005 NIKON CORPORATION



WARNING

TO ENSURE CORRECT USAGE, READ MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT. SOME DOCUMENTATION IS SUPPLIED ON CD-ROM ONLY.



NIKON CORPORATION

Fuji Bldg., 2-3, Marunouchi 3-Chome, Chiyoda-ku,
Tokyo 100-8331, JAPAN
<http://nikonimaging.com/>

En



At the heart of the image

DIGITAL CAMERA
COOLPIX
5600
4600



Compact and Lightweight
3x Optical Zoom-Nikkor Lens
16 Scene Modes



COOLPIX 5600
5.1 effective megapixels



COOLPIX 4600
4.0 effective megapixels