# **New Product Summary**

# **EPSON EB-X72**

The EB-X72 offers friendly design and portable weight. Simple functions allow you to use the projector very easily.

Its exceptional value is complemented by an outstanding 5000 hours long-life lamp, offering you extra peace of mind.

#### No time wasting with quick start up and shut down

Start your presentation from just 5 seconds from power on, to full power! Pack away efficiently with less than 1 second cool down time before the double-beep signals it's safe to unplug and go.

### Connect easily with USB display

This projector is designed for simple operation. Epson's USB Display technology means that by simply connecting the projector to your computer with a USB cable you can show your Presentation and step through your slides or images using the projector remote control.

## Reduce your projection power consumption

Epson's exclusive and patented E-TORL lamp technology, low wattage lamps can be used even for bright output; and coupled with the Epson EB-X72 low power & standby consumption you are sure to save money and stay ecologically friendly!

## **Smart & Friendly Design**

- Compact size and weight: over 30% size reduction compared to its predecessor!
- 3LCD technology for colourful images and high Colour Light Output, 2000 Lumens brightness
- · Quick and Easy set-up: Quick Start-up 5 sec / Instant Off function, A/V mute slide, Easy operation!
- · USB Display: just plug-in and play!
- Low TCO: super affordable projector, 5000 hours E-TORL long-life lamp.\*
- Low standby power consumption (0.4W in Standby)























## **Ordering Information**

Description	EB-X72 - XGA, 3LCD Projector	
Part Number	EB-X72 -	
EAN Codes	EB-X72 –	
Carton Dimensions	383 x 361 x 166 (D x W x H)	
Carton Weight	4.28kg	

The last two letters may vary depending on the version. See the RRP list or Trade Price lists for correct part codes.

<sup>\*</sup>in low brightness mode

# **Screen Size & Projection Distance**

Use the Epson Projection Distance Calculator software available from www.epson.co.uk for distances and screen sizes not shown below.

4 :3

7.0						
	Projection distance					
Screen size	Wide			Tele		
[inch]	cm	inch	foot	cm	inch	foot
30	89	35	2.9	107	42	3.5
40	119	47	3.9	143	56	4.7
50	150	59	4.9	180	71	5.9
60	180	71	5.9	217	85	7.1
80	241	95	7.9	290	114	9.5
100	302	119	9.9	363	143	11.9
150	454	179	14.9	546	215	17.9
200	607	239	19.9	729	287	23.9
250	759	299	24.9	912	359	29.9
300	912	359	29.9	1095	431	35.9

#### Cables

VGA Computer Cable HD-15 to HD-15 1.8m (ELPKC02)

#### V12H005C02

VGA Computer Cable HD-15 to HD-15 3.0m (ELPKC09)

#### V12H005C09

VGA Computer Cable HD-15 to HD-15 20m (ELPKC10)

#### V12H005C10

Component Video Cable (ELPKC19)

### V12H005C19



HD-TV Cable (ELPKC22) V12H005C22



#### Others

Document Camera (ELP DC-06)



### **Accessories**

(model code) order code

### Consumables

Spare Lamp V13H010L54 (ELPLP54)



Air Filter V13H134A25 (ELPAF25)



# Screens

**80" Mobile Screen 16:9 V12H002S2Y** (ELPSC21)

**80" Pantograph Screen 16:10 V12H002S24** (ELPSC24)



Multi-Aspect Screen 65"/74"/80" V13H003S26 (ELPSC26)

# Mountings

Ceiling Plate

Required if using a ceiling pipe. **V12H003B23** (ELPMB23)



Pipe 450mm White V12H003P13 (ELPFP13)



Pipe 700mm White V12H003P14 (ELPFP14)



# What's In The Box

#### **Projector**



**Remote Control** 



2 x AAA Manganese Batteries

for the remote control



Power Cable

1.8 m cable



Computer Cable

Mini D-Sub 15-pin/mini D-Sub 15-pin, 1.8 m (6 ft.)





Document CD-ROM



Password Protect Sticker



**Safety Instructions** 



#### **PRODUCT SPECIFICATIONS**

PROJECTION TECHNOLOGY	3LCD Technology		
RESOLUTION	XGA – 1024 x 768 (4/3 aspect ratio)		
	Up to 1080i		
WHITE LIGHT OUTPUT *	0000 4000		
(Brightness) (Normal/Eco)	2000 – 1960 Lumens		
COLOUR LIGHT OUTPUT	0000 4000		
(Normal/Eco)	2000 – 1960 Lumens		
CONTRAST	2000:1		
IMAGE SIZE	30" to 300"		
	60" screen: 1.80 – 2.17 m (projection distance)		
LENS TYPE	, i		
F-number:	1.58 – 1.72		
Focal Length:	16.9 – 20.28 mm		
Offset:	8:1		
Throw Ratio:	1.48-1.77:1		
ZOOM RATIO	Optical zoom 1-1.2		
NOISE LEVEL (Normal/Eco)	34 dB / 29 dB		
LAMP	7 UD / 23 UD		
Type	475 WILLIE E TODI (FLDLDES)		
Life	175 W UHE – E-TORL (ELPLP54)		
	4000hours / 5000hours		
SOUND	1 x 1 watt		
ADVANCED FEATURES	Security: Padlock and security cable hole, Kensington lock		
	hole, password protection		
	Operation: Direct power on, quick start (5 secs.), instant		
	off		
	Display: 8 colours mode, e-zoom, A/V mute, source		
VIOLIAL INDUIT	search, freeze		
VISUAL INPUT Computer	1 x D-sub 15-pin (RGB), 1 x USB 2.0 type B		
Video	1 x RCA, 1 x S-Video, 1 x Component (D-sub 15-pin)		
AUDIO INPUT	TXTON, TXO VIGOS, TX Component (2 cas to pin)		
Computer / Video	1 x Stereo mini-jack		
AUDIO OUTPUT	, <u> </u>		
Computer	1 x Stereo mini-jack		
WEIGHT	2.3 kg		
DIMENSIONS	228 x 295 x 77 mm		
LANGUAGE	English / French / German / Italian / Spanish / Dutch /		
E/11400/10E	Portuguese / Russian / Swedish / Norwegian / Finnish /		
	Danish / Bulgarian / Polish / Hungarian / Czech / Slovak /		
	Romanian / Croatian / Slovenian / Ukrainian / Catalan /		
	Greek / Turkish / Arabic / Hebrew / Hindi /Japanese /		
	Simplified Chinese / Traditional Chinese / Korean / Thai /		
	Indonesian / Malay / Vietnamese		
POWER CONSUMPTION	On: 234W		
	Standby: 0.4W		
SAFETY REGULATIONS	IEC 60950-1 1st edition (CE marking)		
	EMC directive (89/336/EEC)		
	Recycling regulations		
	, , ,		
WARRANTY	2 years		

<sup>\*</sup> ISO 21118 based measurement





For further information please visit www.epson.co.uk

Trademarks and registered trademarks are the property of Seiko Epson® Corporation or their respective owners.

Product information is subject to change without prior notice.