

FUNCTIONS



SPECIFICATIONS

DIGITAL CAMERA FinePix F402

Number of effective pixels*	2.1 million pixels						
CCD sensor	1/2.7-inch Super CCD in an interwoven pattern (Number of total pixels: 2.11 million pixels)						
Number of recorded pixels	2304 × 1728 (4.0 million)/1600 × 1200/1280 × 960/640 × 480 pixels						
File format	Still image: JPEG (Exif Ver 2.2*)/Movie: AVI (Motion JPEG) [Design rule for Camera File system compliant/DPOF-compatible]						
Storage media	xD-Picture Card (3.3V, 16MB to 128MB)						
Number of images/recording time							
Modes	Still image					Movie	
Image Quality mode displayed	4M (Fine)	4M (Normal)	2M	1M	0.3M	320	160
Number of recorded pixels	2304 × 1728	1600 × 1200	1280 × 960	640 × 480		320 × 240	160 × 120
DPC-16 (16MB)	9	20	39	49	122	Approx. 94 sec.	Approx. 5.0 min.
DPC-32 (32MB)	20	41	79	99	247	Approx. 191 sec.	Approx. 10.1 min.
DPC-64 (64MB)	40	84	159	198	497	Approx. 6.4 min.	Approx. 20.3 min.
DPC-128 (128MB)	81	169	319	398	997	Approx. 12.9 min.	Approx. 40.7 min.

The numbers of images and recording time will vary slightly depending on the type of the subject.

Lens	Fujinon optical fixed-focus lens
Lens focal length	Equivalent to 39mm on a 35mm camera
Focus	TTL contrast-type, autofocus
Focus distance	Normal: Approx. 50 cm/1.6ft. to infinity Macro: Approx. 6 cm – 65 cm/0.2ft. – 2.1ft.
Aperture	F3.2/F8 (Automatically selected)
Exposure control	64-zone TTL metering, Programmed AE (Exposure compensation in manual mode)
Sensitivity	Equivalent to ISO 200, 400 ISO 800, 1600 (Only at 1280 × 960-pixel mode)
Shutter speeds	1/2 to 1/2000 sec.
White balance	Automatic Manual [Fine, Shade, Fluorescent light (Daylight), Fluorescent light (Warm White), Fluorescent light (Cool White), Incandescent light]
Flash	Auto flash using flash control sensor Effective range : 0.3m – 3m/1.0ft. – 9.8ft. Flash mode: Auto, Red-eye Reduction, Forced Flash, Suppressed Flash, Slow Synchro
LCD monitor	1.5-inch low temperature polysilicon TFT (117,000 pixels)
Terminal	USB 1.1 interface, a connection interface with Picture Cradle (Optional)
Power source	Rechargeable Li-ion battery NP-40 or AC Power Adapter included
Dimensions	77 (W) × 69 (H) × 22 (D) mm/3.0 (W) × 2.7 (H) × 0.9 (D) in.
Weight	125g/4.4oz. (excluding battery and media)
Camera functions	
<i>Digital zoom</i>	3.6X (640 × 480 pixels), 1.8X (1280 × 960 pixels), 1.44X (1600 × 1200 pixels)
<i>Shooting modes</i>	Auto, Manual
<i>Continuous shooting mode</i>	Top 2-frame continuous shooting: up to 2 frames at 0.5 sec. intervals
<i>Movie recording</i>	320 × 240 pixels: 10 frames/sec., up to 60 sec. 160 × 120 pixels: 10 frames/sec., up to 240 sec. (with monaural sound, AVI format)
<i>Playback</i>	Single frame (with 14.4X Playback zoom), 9 Multi-frame
<i>Others</i>	Self-timer, DPOF, Protect

- Accessories included**
- 16MB xD-Picture card
 - Rechargeable Lithium-ion Battery NP-40
 - AC-5VS/5VHS
 - Shoulder strap
 - USB cable
 - CD-ROM:
USB driver, FinePix Viewer, DP Editor,
Apple QuickTime™ 5.0, ImageMixer VCD for FinePix



* Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

** Exif 2.2 is a newly revised digital camera file format that contains a variety of shooting information for optimal printing.



Specifications are subject to change without notice.

OPTIONAL ACCESSORIES

	xD-Picture Card DPC-16 (16MB) DPC-32 (32MB) DPC-64 (64MB) DPC-128 (128MB)		Rechargeable Lithium-ion Battery NP-40
	PC Card Adapter DPC-AD		Battery Charger BC-65 • Charges in approx. 2 hours • The NP-40 battery adapter is included.
	Image Memory Card Reader DPC-R1 (USB)		PictureCradle CP-FX402 • AC-input • USB connection
	CompactFlash™ Card Adapter DPC-CF		Soft Case SC-FX402

Microsoft, Windows, and Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. Apple is a registered trademark of Apple Computer Inc. QuickTime and the QuickTime logo are trademarks used under license. The QuickTime logo is registered in the U.S. and other countries. All other trademarks are the property of their respective holders.

For more information on the full range of Fujifilm digital products, please visit our Website: <http://home.fujifilm.com>



FUJI PHOTO FILM CO., LTD.

26-30, NISHIAZABU 2-CHOME, MINATO-KU, TOKYO 106-8620, JAPAN

Ref. No. EB-219E (SK-02-09-DT-MW) Printed in Japan © 2002 Fuji Photo Film Co., Ltd.