

i-3330 SXGA Portable Document Camera Specifications

Model No.	i-3330
Sensor	1/3" CMOS
Total pixel	3 Megapixel
Zoom	9x optical, 8x digital
Frame rate	24
Shooting area	Max: 13.5" x 10.6" /34.3 cm x 26.9 cm Min: 0.1" x 0.1"/0.3 cm x 0.3 cm
Focus	Auto/manual
Native output signal	SXGA(1280x1024)
Converted output signal	XGA, WXGA
Resolution (Horizontal)	≥ 750 TV lines
White balance	Auto/manual
Color adjustment	Yes
Brightness adjustment	Yes
Image capture	Yes, 400 NON-volatile images
Video recording	Yes, with sound
Image mirror	Yes
Image rotation	90°, 180°, 270°
Image split	Yes
Image freeze	Yes
Picture in picture	Yes
Title freeze	Yes
Text mode	Yes
Black and white/color conversion	Yes
OSD	Yes
INPUT TERMINALS	
VGA	x1
AUDIO	x1
OUTPUT TERMINALS	
DVI	x1
VGA	x1
VIDEO	x1
AUDIO	x1
S-VIDEO	x1
OTHER TERMINALS	

USB2.0	Hostx1(Mouse, Memory stick) Slavex1(USB camera/Built-in image download)
USB driver and software	Windows 2000/XP/Vista, Mac OS10.4 or above. Driver plug and play
Remote control	Yes(360°controllable)
Kensington lock	Yes
Built-in LCD screen	Yes
Light source	Embedded LED lamp on arm
Operating temperature	32°F to 104°F (0°C to 40°C)
Dimensions	Folded:12.6"x6.6"x3.7" 32cm x 16.8cm x 9.4cm Setup:19.7"x6.6"x19.3" 50cm x 16.8cm x 49cm
Power supply	12V DC power adapter
Weight(net)	5.5 lbs/2.5Kg

Design and Specifications are subject to change without notice.