

you can  
**Canon**

DIGITAL STILL CAMERA

**DIGITAL  
IXUS II s**

More than  
just a pretty face.



- Ultra compact with a stylish silver-white finish and all-metal body
- 3.2 Megapixels for photo prints up to A4 size
- 2x optical zoom (approx. 6.4x combined)
- Superb image quality and high performance with Canon Visionary Technology
- Advanced 9-point AiAF auto-focus system
- Up to 3-minute movie clips with sound
- PictBridge and Canon Direct Print compatible - no PC required
- Print/Share button for easy direct printing and Windows PC uploading
- Access to CANON iMAGE GATEWAY\* - 100MB free online photo sharing

\*Not available in all regions.



OFFICIAL PARTNER

# Specifications Digital IXUS IIs

<b>IMAGE SENSOR</b> Type Effective Pixels Total Pixels Aspect Ratio Colour Filter Type	1/2.7" CCD Approx. 3.2M Approx. 3.3M 4:3 Primary Colour
<b>IMAGE PROCESSOR</b> Type	DIGIC with iSAPS technology
<b>LENS</b> Focal Length Zoom Maximum f/number Construction	5.4 - 10.8mm (35mm film equivalent: 35 - 70mm) Optical 2x, digital approx. 3.2x, combined approx. 6.4x f/2.8 - f/3.9 6 elements in 6 groups (3 aspherical elements)
<b>FOCUSING</b> Type AF System/Points AF Modes Selected AF Point Display AF Lock AF Assist Beam Closest Focusing Distance	TTL 9-point AiAF, 1-point AF (Fixed centre) Normal, Macro, Infinity YES YES YES 10cm
<b>EXPOSURE CONTROL</b> Metering Modes AE Lock Exposure Compensation ISO Speed Equivalent	Evaluative, Centre-weighted average, Spot (centre) YES +/- 2 EV in 1/3 stop increments AUTO, 50, 100, 200, 400
<b>SHUTTER</b> Type Speed	Mechanical shutter & Electronic shutter 15 - 1/1,500 sec (Shutter speeds of 1 - 15 sec are manually selected with the long-shutter mode, in Manual mode. Shutter speeds of 1.3 sec and more operate with noise reduction.)
<b>WHITE BALANCE</b> Type Settings	TTL Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
<b>VIEWFINDER</b> Viewfinder Eyepoint	Real-image zoom, optical viewfinder 16mm
<b>LCD MONITOR</b> Monitor Coverage Brightness	1.5" P-Si TFT, approx. 118,000 pixels 100% 15 levels
<b>FLASH</b> Modes Slow Sync Speed Red-eye Reduction Flash Exposure Lock Built-in Flash Range	Auto, Manual Flash On/Off YES YES YES 47cm - 3.0m (W)/47cm - 2.0m (T) (at ISO AUTO equivalent)
<b>SHOOTING</b> Modes Photo Effects Continuous Shooting	Auto, Manual, Stitch Assist, Movie Vivid, Neutral, Low Sharpening, Sepia, Black & White Approx. 2.2 fps <sup>1</sup> (speed maintained for up to 12 images)
<b>RECORDING PIXELS/ COMPRESSION</b> Image Size Compression Movies Movie Length	(L)2048 x 1536, (M1)1600 x 1200, (M2)1024 x 768, (S)640 x 480 SuperFine, Fine, Normal (L)640 x 480, (M)320 x 240, (S)160 x 120, 15 fps Up to 30 sec (640 x 480); Up to 3 mins (320 x 240, 160 x 120) depending upon resolution and memory card capacity

<b>FILE FORMAT</b> Still Image Format Movies Sound Files	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant AVI [Motion JPEG + WAVE (monaural)] WAVE (monaural)
<b>DIRECT PRINT</b> Canon Printers PictBridge	Canon Compact Photo Printers (ID Photo Print, Movie Print) and Bubble Jet Printers with the direct print function YES
<b>OTHER FEATURES</b> My Camera Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Display Formats Image Erase Protection Image Erase Self Timer Menu Languages	Start-up image and camera sounds customisation Up to 60 sec per image YES YES 2x - 10x Single/Index (9 thumbnail images)/Slide Show/Magnified/Movie Single image Single Image, All 2 or 10 sec English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Chinese, Japanese
<b>INTERFACE</b> Computer Other	USB (PTP) A/V output (PAL/NTSC)
<b>MEMORY CARD</b> Type	Secure Digital (SD) Card
<b>SUPPORTED OPERATING SYSTEM</b> PC Macintosh	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2
<b>SOFTWARE</b> Browsing & Printing Other Drivers Image Manipulation	ZoomBrowser EX (PhotoRecord)/ImageBrowser PhotoStitch TWAIN (Windows 98/2000), WIA (Windows Me) ArcSoft PhotoImpression, ArcSoft VideoImpression
<b>POWER SOURCE</b> Batteries Battery Life Power Saving A/C Power Supply	Rechargeable Li-ion Battery NB-3L (battery and charger supplied) Approx. 210 shots (LCD monitor on) Approx. 550 shots (LCD monitor off) Approx. 180 mins replay time YES CA-PS500 optional (DC coupler DR-900 is required)
<b>ACCESSORIES</b> Case Waterproof/ Weatherproof Case Power Supply & Battery Chargers	Soft Case SC-DC20 Waterproof Case (40m) WP-DC10 Compact Battery Charger CB-2LUE, AC Power Adapter ACK900
<b>PHYSICAL SPECIFICATIONS</b> Operating Environment Dimensions (WxHxD) Weight (body only)	0 - 40°C, 10 - 90% humidity 85.0 x 56.0 x 23.9mm Approx. 165g

<sup>1</sup> Large/Fine with LCD monitor off

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

**3.2**  
MEGA  
PIXELS

**6.4x**  
ZOOM  
Optical & Digital  
Combined

**DIGIC**

**Movie**

**PictBridge**

**DIRECT PRINT**

**BUBBLE JET DIRECT**

**Print/Share BUTTON**

**9-point AiAF**

**CANON IMAGE GATEWAY**

**Exif Print**

**DPOF**

**Designed for**  
Microsoft®  
Windows® XP

you can  
**Canon**

Canon Inc  
www.canon.com

Canon Europa NV  
www.canon-europe.com

0041W783 © Canon Europa NV 2004

Canon Digital  
Creators Contest 2004  
The international digital imaging contest  
www.canon.com/cdccc

**WWF**  
Canon Europa NV  
Conservation Partner