



Overview

The ViewSonic PJD7822HDL is a Full HD home entertainment projector. Equipped with 3,200 ANSI lumens and a 15,000:1 contrast ratio, this projector can display clear, bright images even in rooms with high ambient light. In addition, a short throw lens with 1.3x optical zoom offers flexible setup options for smaller rooms. With Dual HDMI inputs and a USB charging port, the PJD7822HDL offers flexible connectivity to high-definition devices, as well as compatibility with wireless HDMI dongles such as Google Chromecast. The PJD7822HDL also includes 3D compatibility, an integrated speaker, and SuperColor™ technology for a wider color range and true-to-life image projection.



**Full HD 1080p Delivers The
Finest Picture Quality**



2x HDMI Inputs

This ViewSonic projector features Full HD 1920x1080

Equipped with dual HDMI inputs, this projector

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic®
See the difference™ 

PJD7822HDL

Full HD 3,200 Lumens Home Entertainment Projector

(1080p) native resolution for delivering exceptional detail and astonishing clarity. It's perfect for watching all types of high definition content, including movies, videos, sports, games, and TV, without any distortion or scaling of the original video format.

delivers the highest picture and sound quality from just one cable per source. It's perfect for connecting to any HDMI-enabled devices such as computers, media players, game consoles, Blu-ray® and DVD players.



USB Port for Media Streaming Dongles

Wireless HDMI dongles such as Google Chromecast, can be plugged into the projector's HDMI port while being powered by the projector's USB port. Simply use an Android phone, tablet, iPhone®, iPad®, Mac® or Windows® laptop to cast your favourite entertainment and apps right onto the big screen.

Bright Images for Any Environment

Packed with 3,200 lumens and a high contrast ratio of 15,000:1, this projector is guaranteed to produce bright images in any environment – even in rooms with high ambient light. That means you can still watch your favourite sports matches during the day, without having to close the curtains.



For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic
See the difference™ 

Project Large Images in Small Places

The reduced-throw lens enables large images to be projected from short distances in small rooms. Images 60-inches in width can be displayed from only 5 feet away.



1.3x Optical Zoom Lens

Equipped with a 1.3x optical zoom lens, the PJD7822HDL provides mounting flexibility with a wider throw distance range. This zoom lens also enables the projector to project images up to 20% larger than a conventional projector equipped with a 1.1x lens.



SuperColor: Best in Class Colour Accuracy

ViewSonic's exclusive SuperColor Technology offers a wider colour range than conventional projectors. With an exclusive colour wheel design and dynamic lamp control capabilities, SuperColor Technology projects images with reliable and true-to-life color performance, in all environments.




Technology Used in Hollywood

Advanced Digital Light Processing technology allows you to experience lifelike images with the same projection technology used by Hollywood filmmakers. And with no air filters to clean or change, the latest generation of projectors from ViewSonic are among the lowest TCO (Total Cost of Ownership) in the industry.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic®
See the difference™ 



SuperColor™ projectors vs. Conventional projectors



SuperColor™ projectors offer color accuracy levels



Conventional projectors offer low-quality images

Technical Specifications

Display	Type	TI 0.65 1080p DMD, LVDS S600 DMD
	Optimum Resolution	1920(H) x 1080(V).
	Contrast Ratio	15,000:1 (Max; with Dynamic Eco) 2,200:1 (Typ; w/o DCR) 2,000:1 (Min; w/o DCR)
	Aspect Ratio	16:9
	Colour Depth	1.07 Billion Colours (30 bits per color)
	Optical Zoom	1.3X
	Optical Offset	110%±5%
	Display Size (inch)	30~300(Visible)
	Throw Ratio	1.15~1.5 (60" @ 1.52m)
	Throw Distance (m)	1.0 ~ 10
	Keystone Correction	+40~-40°, vertical (Manual)
	Lamp Power (watt)	210W

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

Lamp Life (Normal/
ECO/ Dynamic) 5000 / 6000 / 8000 hrs

CONNECTOR INPUT

RGB (VGA/ D-Sub) DB-15 x1 ; Supports Component Video via DB-15
Composite Video RCA-1 x1
Component Video Share with RGB (x2)
S-Video Mini-Din 4 pin (x1)
Audio (PC Audio,
Analog) 3.5mm Mini-Mono Jack (x1)
HDMI 1.4 *2
Type A USB x 1 (5V / 1A)
Mini USB x 1

CONNECTOR OUTPUT

RGB (VGA/ D-Sub) DB-15 x1
PC Audio, Analog 3.5mm Mini-Mono Jack (x1)

INPUT SIGNAL

Video NTSC: NTSC M (3.58 MHz), 4.43MHz PAL: PAL (B, D, G, H, I, M, N, 60)
SECAM: SECAM (B, D, G, K, K1, L) SD: 480i and 576i ED: 480p and 576p
HD: 720p,1080i,1080p
Frequency (Horizontal /
Vertical) 15~100 kHz / 24~120 Hz

PC COMPATIBILITY

PC Timing Analog , 1920x1080@60Hz (native)
Mac® Timing Support up to 1920x1200@60Hz (same as in PC), Analog (*MAC adapter
maybe required)

SPEAKER

2W x 1

POWER

Voltage 100~240Vac 50/60Hz (Auto Switching)
Consumption 290W Max. 264W Typ. 210W Min. < 0.5W.(Under condition: Power Saving
On)

OPERATING CONDITIONS

Temperature (° F / ° C) 0°~40°C / 32°~104°F
Humidity 10~90%, Non-Condensation
Altitude 0~6,000 ft, operational up to 10,000 ft at reduced reliability and
performance

NOISE LEVEL

Normal / Eco-mode 35dB / 29dB

DIMENSIONS (W x H x D)

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic®
See the difference™ 

Physical (inch / mm)	10.55 x 3.32 x 8.70 x / 268 x 84.4 x 221
Packaging (inch / mm)	14.17 x 12.80 x 7.40 / 360 x 325 x 188

WEIGHT	Net (lb / kg)	4.63 / 2.1
	Gross (lb / kg)	7.48 / 3.4

REGULATIONS	Standard	CB
--------------------	----------	----

WARRANTY	**Warranty offered may differ from market to market	
-----------------	---	--

What's in the box?

1. Power Cord, 1.8m, black x 1
 2. VGA Cable, 1.8m, black x 1
 3. Remote Control with AAA Batteries
 4. Quick Start Guide x1
 5. ViewSonic DVD Wizard x 1
 6. Warranty card & sticker (VSCN only)
- *Actual content may differ from market to market

ViewSonic® Limited Warranty

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

