



PT-D5700
PT-D5700L*1



PT-DW5100
PT-DW5100L*1



Conference

0.7" DLP™ chip x 1
275 W UHM™ x 2
6,000 lumens
F 1.7–2.0, f 25.6–33.8 mm (1.8–2.4:1)
2,000:1
XGA/UXGA
15–91 kHz/50–85 Hz
PAL, PAL-M, PAL-N, PAL60, SECAM, NTSC, NTSC 4.43
50"–600" (50"–600" with the ET-DLE050)
Vertical: +50%, horizontal: ±10%
Vertical ±30°
13.9 kg/30.6 lbs (PT-D5700L: 13.1 kg/28.9 lbs)
530 x 167 x 441 mm*2 (20-7/8" x 6-9/16" x 17-3/8") *2
750 W (770 W for North America)
DVI-D (24-pin x 1, HDCP-compatible)
RGB (D-sub HD 15-pin x 1, 5BNC x 1)
Composite video (BNC x 1)
S-Video (Min-DIN 4-pin x 1)
Serial (D-sub 9-pin x 1 (in), D-sub 9-pin x 1 (out), RS-232C)
Remote (D-sub 9-pin x 1 (in), M3 x 1 (in), M3 x 1 (out))
LAN (RJ-45 x 1, 10Base-T/100Base-TX)

Conference

0.65" DLP™ chip x 1
275 W UHM™ x 2
5,500 lumens
F 1.7–2.0, f 25.6–33.8 mm (1.8–2.4:1)
2,000:1
WXGA (1,280 x 768)/UXGA
15–91 kHz/50–85 Hz
PAL, PAL-M, PAL-N, PAL60, SECAM, NTSC, NTSC 4.43
50"–600" (50"–600" with the ET-DLE050)
Vertical: +60%, horizontal: ±10%
Vertical ±30°
13.9 kg/30.6 lbs (PT-DW5100L: 13.1 kg/28.9 lbs)
530 x 167 x 441 mm*2 (20-7/8" x 6-9/16" x 17-3/8") *2
750 W (770 W for North America)
DVI-D (24-pin x 1, HDCP-compatible)
RGB (D-sub HD 15-pin x 1, 5BNC x 1)
Composite video (BNC x 1)
S-Video (Min-DIN 4-pin x 1)
Serial (D-sub 9-pin x 1 (in), D-sub 9-pin x 1 (out), RS-232C)
Remote (D-sub 9-pin x 1 (in), M3 x 1 (in), M3 x 1 (out))
LAN (RJ-45 x 1, 10Base-T/100Base-TX)

ET-LAD57
ET-LAD57W (2 units)

ET-LAD57
ET-LAD57W (2 units)

ET-PKD56H (High ceiling mount bracket)
ET-PKD55S (Low ceiling mount bracket)

ET-PKD56H (High ceiling mount bracket)
ET-PKD55S (Low ceiling mount bracket)

ET-DLE100 (Zoom lens, 1.3–1.8:1)
ET-DLE200 (Zoom lens, 2.4–4.0:1)
ET-DLE300 (Zoom lens, 3.8–6.0:1)
ET-DLE400 (Zoom lens, 5.8–8.1:1)
ET-DLE050 (Fixed-focus lens, 0.8:1)

ET-DLE100 (Zoom lens, 1.4–1.8:1)
ET-DLE200 (Zoom lens, 2.5–4.1:1)
ET-DLE310 (Zoom lens, 3.5–4.7:1)
ET-DLE410 (Zoom lens, 4.7–8.9:1)
ET-DLE050 (Fixed-focus lens, 0.8:1)

Power cord, Wireless/wired remote control, Batteries for remote control unit, Wire rope
BriteOptic™ dual lamp system, Vivid colour control, 3D colour management system, Dust proof design, Liquid cooling system, Edge blending, Direct power off, Anti-theft functions, Wired LAN system, PJLink™

Power cord, Wireless/wired remote control, Batteries for remote control unit, Wire rope
BriteOptic™ dual lamp system, Vivid colour control, 3D colour management system, Dust proof design, Liquid cooling system, Edge blending, Direct power off, Anti-theft functions, Wired LAN system, PJLink™