



3GPP/ISMA Pan/Tilt Network Camera



The VIVOTEK PT7135/PT7137 is a 3GPP/ISMA-compatible pan/tilt network camera, offering superior image quality and optimized bandwidth efficiency by MPEG-4 implementation. Users can easily access it and receive synchronized video and audio by computers, cellphones, or media adapters with TV, anytime, anywhere for indoor surveillance and remote monitoring.





PT7135 / PT7137

Features

- Live Video and Audio Monitoring via 2.5G/3G Mobile Phone or Media Adapter
- Motorized Wide-Range Pan/Tilt
- MPEG-4 Video Compression (Simple Profile)
- Compact Size with Stylish Design
- Easy to Install and Configure
- Optimized Synchronization of Audio and Video
- 802.11g Wireless Connection (PT7137)
- Supports 3GPP/ISMA RTSP (Real Time Streaming Protocol)
- Intelligent Motion Detection
- Superior Low Light Performance
- Excellent Image Quality with Up to 30 Frames Per Second in Full VGA Resolution

Pan/Tilt Network Camera

PT7135 / PT7137



Technical Specifications

Models	<ul style="list-style-type: none"> PT7135 (CMOS) PT7137 (CMOS, wireless) 	Pan/Tilt	<ul style="list-style-type: none"> Pan: range 350° (+175°~-175°) Tilt: range 125°(+90°~-35°) Auto pan mode Auto patrol mode
System	<ul style="list-style-type: none"> CPU: VVTK-1000 SoC RAM: 32MB SDRAM ROM: 4MB FLASH ROM 	Microphone	<ul style="list-style-type: none"> Omni-directional Frequency: 50~16000Hz S/N ratio: More than 60dB
Networking	<ul style="list-style-type: none"> Protocols: UPnP, TCP/IP, RTSP/RTP/RTCP, HTTP, SMTP, FTP, Telnet, NTP, DNS, DDNS, DHCP and PPPoE Ethernet: 10 baseT or 100 baseT Fast Ethernet auto negotiation Wireless (PT7137): 802.11g wireless LAN 	Security	<ul style="list-style-type: none"> ID/Password authentication
Video	<ul style="list-style-type: none"> Algorithm: MPEG4 simple profile for streaming video, JPEG for still image Features: Adjustable image size, quality and bit-rate; Time stamp and text caption; Three configurable motion detection windows; Flip & mirror Resolution: Up to 30/25 frames at 160x120; Up to 30/25 frames at 176x144; Up to 30/25 frames at 320x240; Up to 30/25 frames at 640x480 	LED Indicator	<ul style="list-style-type: none"> System power and status indicator System activity and Network link indicator Microphone status indicator
Camera Specifications	<ul style="list-style-type: none"> 1/4" color CMOS sensor Resolution: 640(H)x480(V) 1.0Lux/F2.0 AGC/AWB/AES Electronic Shutter: 1/60 to 1/15,000 sec. 	Dimensions	<ul style="list-style-type: none"> Depth: 110mm Width: 110mm Height: 130mm
Lens	<ul style="list-style-type: none"> 4.0mm, F2.0 	Weight	<ul style="list-style-type: none"> Net: 259g (PT7135) Net: 271g (PT7137)
Audio	<ul style="list-style-type: none"> Algorithm: GSM-AMR/MPEG4 AAC Supports audio mute 	Power	<ul style="list-style-type: none"> 12VDC
		Operating Environments	<ul style="list-style-type: none"> Temperature: 0~40°C (32~102°F) Humidity: 85% RH
		EMI & Safety	<ul style="list-style-type: none"> CE, FCC
		Viewing System Requirements	<ul style="list-style-type: none"> Operating system: Microsoft Windows 98 SE, ME, 2000, XP Browser: Internet Explorer 5.0 or above Cellphone: 3GPP player Real Player 10.5 Quick Time 6.5 Packet Video Player 3.0

All specifications are subject to change without notice.
All other trademarks are owned by their respective companies.



6F, No.192, Lien-Cheng Rd., Chung-Ho, Taipei County, Taiwan
Tel: +886 2 82455282
Fax: +886 2 8245532
E-mail: sales@vivotek.com
Http://www.vivotek.com

