



you can
Canon

PowerShot S1 IS



you can
Canon



OFFICIAL PARTNER



Canon Inc
www.canon.com

Canon Europa NV
www.canon-europe.com

0040W244
© Canon Europa NV 2004

Stills and movies
that get you closer...

Essential accessories.

With the PowerShot S1 IS's excellent range of optional accessories, you can expand your still image and movie portfolio potential, as you increase your skill with the camera.

SUPPLIED WITH CAMERA



OPTIONAL LENS ACCESSORIES



TC-DC52B
1.6x Tele Converter



Approx. 608mm equivalent with tele converter



380mm equivalent



WC-DC52A
0.7x Wide Converter



38mm equivalent



LAH-DC10
Lens Adaptor/
Hood Set



Approx. 26.6mm equivalent with wide converter

OPTIONAL ACCESSORIES



WP-DC20
Waterproof Case



SC-DC40
Soft Case



FC-512MSH
Fast CF-card



2GB Hitachi
Microdrive



CBK4-200 NiMH
Battery/Charger Kit
(includes a battery charger and 4 NiMH NB4-200 batteries)



CA-PS700
AC Adaptor Kit



WL-DC100
Wireless controller



Canon Photo Printers
- Compact Photo Printers
- Bubble Jet Direct Printers
- Bubble Jet Printers



Compliant with all PictBridge compatible printers

Specifications PowerShot S1 IS

IMAGE SENSOR Type Effective Pixels Total Pixels Aspect Ratio Colour Filter Type	1/2.7" CCD Approx. 3.2M Approx. 3.3M 4:3 Primary Colour
IMAGE PROCESSOR Type	DIGIC with iSAPS technology
LENS Focal Length Zoom Maximum f/number Construction Image Stabilisation Ultrasonic Motor (USM)	5.8 - 58.0 (35mm film equivalent: 38 - 380mm) Optical 10x, digital approx. 3.2x, combined approx. 32x f/2.8 - f/3.1 11 elements in 9 groups (1 aspherical element) YES (shift-type) YES, zoom
FOCUSING Type AF System/Points AF Modes AF Point Selection Selected AF Point Display AF Lock Manual Focus Focus Bracketing Closest Focusing Distance	TTL 1 point AF (any position is available) Single, Continuous Manual Selection using flexizone Indicated in viewfinder or on rear LCD panel Locked when shutter button is pressed half way YES YES YES 10cm
EXPOSURE CONTROL Metering Modes AE Lock Exposure Compensation AEB ISO Speed Equivalent	Evaluative, Centre-weighted average, Spot (centre or linked to focusing frame) YES +/- 2 EV in 1/3 stop increments 1/3 - 2 EV in 1/3 stop increments AUTO, 50, 100, 200, 400
SHUTTER Type Speed	Mechanical shutter & electronic shutter 15 - 1/2,000 sec. (Slow Shutter speeds of 1.3sec. and more, available in Manual and Shutter Priority AE modes only. Shutter speeds of 1.3 sec. and more operate with noise reduction)
WHITE BALANCE Type Settings	TTL Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Flash, Custom
COLOUR MATRIX Type	sRGB
VIEWFINDER Viewfinder Coverage (Vertical/Horizontal) Eyepoint Dioptre Correction Viewfinder Information	EVF (0.33" type), approx. 114,000 pixels 100% 10mm -5.5 - 1.5 dpt Full Information
LCD MONITOR Monitor Coverage Brightness	Vari-angle 1.5" P-Si TFT, approx. 114,000 pixels 100% 2 levels
FLASH Modes Slow Sync Speed Red-eye Reduction Flash Exposure Compensation Flash Exposure Lock Manual Power Adjustment Second Curtain Synchronisation Built-in Flash Range	Auto, Manual Flash On/Off YES YES +/- 2 EV in 1/3 stop increments YES 3 levels with internal flash YES 1.0-4.2m (W)/1.0 - 3.8m (T) (at ISO 100 equivalent)
SHOOTING Modes Photo Effects Drive modes Continuous Shooting Intervalometer	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Custom, Portrait, Landscape, Night Scene, Fast Shutter, Slow Shutter, Stitch Assist, Movie Vivid, Neutral, Low Sharpening, Sepia, Black & White, Custom effect Single, Continuous Approx. 1.7 images/sec. Speed maintained up to 24 images (Large/Fine mode. Depending upon CF card speed and capacity) Up to 100 shots in 1 - 60 minute increments

RECORDING PIXELS/ COMPRESSION Image Size Compression Movies Movie Length	(L)2048 x 1536, (M1)1600 x 1200, (M2)1024 x 768, (S)640 x 480 Superfine, Fine, Normal (LF)640 x 480 Fine, (L)640 x 480, (M)320 x 240 30fps or 15fps available 1GB or 60min. (dependant on CF card speed and capacity)
FILE FORMAT Still Image Format Movies Sound Files	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant AVI [Motion JPEG + WAVE (monaural)] WAVE (monaural)
DIRECT PRINT Canon Printers PictBridge	Canon Compact Photo Printers and Bubble Jet Printers with the direct print function YES
OTHER FEATURES My Camera Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Display Formats Image Erase Protection Image Erase Self Timer Menu Languages	Start-up image and camera sounds customisation Up to 60 sec. per image YES YES 2x - 10x Single/Index (9 thumbnail images)/Slide Show/Magnified/Movie Single Image Single, All Approx. 2 or 10 sec. English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Japanese
INTERFACE Computer Other	USB (Mini-B, PTP) A/V output (PAL/NTSC)
MEMORY CARD Type	CompactFlash Type I / II (Microdrive compatible)
SUPPORTED OPERATING SYSTEM PC Macintosh	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2
SOFTWARE Browsing & Printing Other Drivers Image Manipulation	ZoomBrowser EX (PhotoRecord)/ImageBrowser PhotoStitch TWAIN (Windows 98/2000), WIA (Windows Me) ArcSoft PhotoStudio, ArcSoft VideoImpression
POWER SOURCE Batteries Battery life Power saving A/C Power Supply	4x AA-size Alkaline Batteries included Alkaline Batteries: Approx. 120 shots (LCD monitor on), Approx. 125 shots (Viewfinder on) Approx. 330 min. (Playback) NiMH Batteries (NB-2AH): Approx. 550 shots (LCD monitor on), Approx. 570 shots (Viewfinder on) Approx. 450min. (Playback) Power turns off after 10, 20, 30sec. 1, 2, 3mins. Compact power adapter CA-PS700 (optional)
ACCESSORIES Case Waterproof Case Lenses Remote Controller/Switch Power Supply & Battery Chargers	SC-DC40 Soft Case (40m) WP-DC20 Tele Converter 1.6x TC-DC52B Wide Converter 0.7x WC-DC52A Lens Adaptor/Hood set LAH-DC10 Wireless Controller WL-DC100 Compact AC power adaptor CA-PS700 Battery Charger Kit CBK-100, CBK4-200
PHYSICAL SPECIFICATIONS Operating Environment Dimensions (WxHxD) Weight (body only)	0 - 40°C, 10 - 90% humidity 111.0 x 78.0 x 66.1mm (excluding viewfinder-eyepiece & protrusions) Approx. 370g

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

**3.2MEGA
PIXELS**

**10x
ZOOM
Optical**

**OPTICAL
IMAGE
STABILIZER**

ULTRASONIC

**Movie
30fps / VGA**

DIGIC

PictBridge

**DIRECT
PRINT**

**BUBBLE JET
DIRECT**

**FlexiZone AF/AE
CONTROL**

**CANON
IMAGE
GATEWAY**

Exif Print

DPOF

**Designed for
Microsoft®
Windows®XP**