

you can
Canon

PowerShot Pro1



Don't compromise.




OFFICIAL PARTNER

Equipped for anything.

The PowerShot Pro1 has the tools to tackle any job.

The PowerShot Pro1 offers the most extensive array of accessories in the Canon PowerShot range of digital cameras, enabling you to be as creative as you want.



By enabling the converter mode when installing optical accessories such as the TC-DC58A tele-converter lens and 500D close-up lens, the lens will automatically move to the optimum zoom position.

SPEEDLITES



CONVERSION LENSES



58MM FILTERS



SC-DC30 Soft Case



MicroDrives (Hitachi)



PCMCIA Card adapter

Speedlite 550EX



Speedlite 420EX



Speedlite 220EX



Speedlite Transmitter ST-E2

KIT CONTENTS



AVC-DC300 A/V Cable



TV/Video

IFC-400PCU USB Interface Cable



DIRECT PRINTERS



Canon Compact Photo Printers


• CP-300

• CP-200



Canon Bubble Jet Direct Photo Printers

- BJ i9950
- BJ i990
- BJ i965
- BJ i905D
- BJ i865
- BJ i560
- BJ i475D
- BJ i455
- BJ i80



Compliant with all PictBridge compatible printers

PC/Mac



CF Card FC-64MH



BP-511A Rechargeable Li-ion Battery



CB-5L Battery Charger

DIF-100 Direct Interface Cable*

- Card Photo Printer CP-100
- Card Photo Printer CP-10

*Supplied with printer

DIF-B100 Direct Interface Cable*

- BJ S830D
- BJ S820D
- BJ S530D



Canon CF Cards

- FC-512MSH
- FC-256MH
- FC-128M
- FC-96M
- FC-64MH



BP-511A/BP-511 Rechargeable Li-ion Battery

AC POWER SUPPLY ACCESSORIES



- CG-570 Battery Charge Adaptor (charges 2 batteries in series)
- CB-570 Car Battery Cable (for CG-570)
- CA-560 Compact Power Adaptor (for CG-570)
- CB-5L Battery Charger (charges a single battery)



Specifications PowerShot Pro1

IMAGE SENSOR Type Effective Pixels Total Pixels Aspect Ratio Colour Filter Type	2/3" CCD Approx. 8.0M Approx. 8.3M 4:3 Primary Colour
IMAGE PROCESSOR Type	DIGIC with iSAPS technology
LENS Focal Length Zoom Maximum f/number Construction Ultrasonic Motor (USM)	7.2 – 50.8 mm (35mm film equivalent: 28 – 200mm) Optical 7.0x, digital approx. 3.2x, combined approx. 22x f/2.4 - f/3.5 14 elements in 10 groups, L-series lens (1 Fluorite, 1 UD glass & 2 aspherical elements) YES, zoom
FOCUSING Type AF System/Points AF Modes AF Point Selection Selected AF Point Display AF Lock Manual Focus Focus Bracketing Closest Focusing Distance	Hybrid AF (TTL and external systems) 1 point AF (any position is available) Single, Continuous Manual selections using flexizone Indicated in viewfinder or on rear LCD panel Locked when shutter button is pressed half way YES YES 3cm (in Super Macro mode)
EXPOSURE CONTROL Metering Modes AE Lock Exposure Compensation AEB ISO Speed Equivalent	Evaluative, Centre-weighted average, Spot (centre or linked to focusing frame) YES +/- 2 EV in 1/3 stop increments 1/3 – 2 EV in 1/3 stop increments AUTO, 50, 100, 200, 400
SHUTTER Type Speed	Mechanical shutter & electronic shutter 15 - 1/4,000 sec. (Slow shutter speeds of 1.3 sec. and more available in Manual and Shutter Priority AE Modes only. Shutter speeds of 1.3 sec. and more operate with noise reduction)
WHITE BALANCE Type Settings	TTL Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Flash, Custom (2)
COLOUR MATRIX Type	Two types of colour space, sRGB and Adobe RGB
VIEWFINDER Viewfinder Coverage (Vertical/Horizontal) Eyepoint Dioptre Correction Viewfinder Information	EVF (0.44"), approx. 235,000 pixels 100% 12mm -5.5 – 1.5 dpt Full information
LCD MONITOR Monitor Coverage Brightness	Vari-angle 2.0" P-Si TFT, approx. 235,000 pixels 100% Adjustable to 1 of 2 levels
FLASH Modes HotShoe/ PC terminal X-sync Slow Sync Speed Red-eye Reduction Flash Exposure Compensation Flash Exposure Lock Manual Power Adjustment Second Curtain Synchronisation Built-in Flash Range External Flash	Auto, Manual Flash On/Off YES/- 1/250 sec. YES YES +/- 2 EV in 1/3 stop increments YES 3 levels with internal flash (13 levels with external EX Speedlites) YES 50cm-5.0m (W)/1.0m – 3.5m (T) (at ISO 100 equivalent) E-TTL with EX series Speedlites, wireless multi-flash support
SHOOTING Modes Photo Effects Drive modes Continuous Shooting Intervalometer	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Custom (2), Portrait, Landscape, Night Scene, Stitch Assist, Movie Vivid, Neutral, Low Sharpening, Sepia, Black & White, Custom Single, Continuous High Speed at approx. 2.5 fps ¹ (speed maintained for up to 6 images) Normal at approx. 1.0 fps ¹ (speed maintained for up to 18 images) Up to 100 shots in 1 – 60 minute increments ²

RECORDING PIXELS/ COMPRESSION Image Size Compression Movies Movie Length	(L)3264x2448, (M1)2272x1704, (M2)1600x1200, (M3)1024x768, (S)640x480, (RAW)3504x2336 Superfine, Fine, Normal or RAW (Recording pixels not selectable) 640x480, 320x240, 160x120, 15fps Up to 30 seconds (640x480) ² Up to 3 minutes (320x240, 160x120) ²
FILE FORMAT Still Image Format Movies Sound Files	JPEG (Exif 2.21 [Exif Print] compliant)/Design rule for Camera File system, RAW, Digital Print Order Format [DPOF] Version 1.1 compliant AVI [Motion JPEG + WAVE (monaural)] WAVE (monaural)
DIRECT PRINT Canon Printers PictBridge	Canon Compact Photo Printers and Bubble Jet Printers with the Direct Print Function YES
OTHER FEATURES LCD Panel (EL) Illumination My Camera Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Display Formats Image Erase Protection Image Erase Self Timer Menu Languages	YES Start-up image and camera sounds customisation Up to 60 sec. per image YES YES 2x – 10x Single/Index (9 thumbnail images)/Slide Show/ Magnification/Movie Single image Single image, all Approx. 2 or 10 sec. English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Japanese
INTERFACE Computer Other	USB (Mini-B, PTP) A/V output (PAL/NTSC)
MEMORY CARD Type	CompactFlash Type I/II (MicroDrive compatible) ³
SUPPORTED OPERATING SYSTEM PC Macintosh	Windows 98 (including SE)/2000/Me/XP OS 9.0 – 9.2, OS X v10.1/v10.2
SOFTWARE Browsing & Printing Other Drivers Image Manipulation	ZoomBrowser EX (PhotoRecord)/ImageBrowser PhotoStitch TWIN (Windows 98/2000), WIA (Windows Me) ArcSoft PhotoStudio, ArcSoft VideImpression
POWER SOURCE Batteries Battery life Power saving A/C Power Supply	Rechargeable Li-ion Battery BP-511A/BP-514/BP-511/BP-512 (BP-511A battery and charger supplied) Approx. 420 shots (LCD monitor on) Approx. 420 shots (Electronic viewfinder on) Approx. 400 min. (Playback) Power turns off after 10, 20, 30 sec, 1, 2, 3 mins. Compact power adapter CA-560
ACCESSORIES Case Lenses Flash Remote Controller/Switch Power Supply & Battery Chargers	SC-DC30 Soft Case Tele-converter TC-DC58A/Lens hood LH-DC58A/ Conversion Lens Adaptor LA-DC58C/Filter Adaptor FA-DC58A Canon Speedlites (220EX, 380EX, 420EX, 550EX, Macro-Ring-Lite MR-14EX, Macro Twin Lite MT-24EX, Speedlite Transmitter ST-E2) Wireless Controller WL-DC100 (supplied) AC Power Adaptor CA-560, Battery Charger (single) CB-5L (supplied in camera kit), Battery Charger (Twin) CG-560/570/580, Car Battery Adaptor CR-560, Car Battery Cable CB-560/570
PHYSICAL SPECIFICATIONS Body Materials Operating Environment Dimensions (WxHxD) Weight (body only)	Plastic 0 – 40°C, 10 – 90% humidity 117.5x72.0x90.3mm (excluding viewfinder-eyepiece & protrusions) approx. 545g
<p>1 Large/Fine with LCD monitor off 2 Depending upon CF card speed and capacity 3 Compatible with 2GB memory cards and larger</p> <p>Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.</p>	

8.0 MEGA PIXELS

22x ZOOM
Optical & Digital Combined

28mm* WIDE ZOOM
*35mm equivalent

FLUORITE L Lens

ULTRASONIC

Hybrid AF

DIGIC

FlexiZone AF/AE CONTROL

PictBridge

DIRECT PRINT

BUBBLE JET DIRECT

CANON IMAGE GATEWAY

Exif Print

DPOF

Designed for Microsoft® Windows® XP

you can
Canon

Canon Inc
www.canon.com

Canon Europa NV
www.canon-europe.com

0040W263 © Canon Europa NV 2004

Canon Digital
Creators Contest 2004
The international digital imaging contest
www.canon.com/ccc2
Take On the World!
Create A New Digital Imaging World.

